

# 68V, 80A, 7.2mΩ N-channel Power Trench MOSFET

## JMTC6888A

### Features


- Excellent  $R_{DS(ON)}$  and Low Gate Charge
- 100% UIS Tested
- 100%  $\Delta V_{ds}$  Tested
- Halogen-free; RoHS-compliant

### Applications


- Load Switch
- PWM Application
- Power Management

### Product Summary


Parameters	Value	Unit
$V_{DSS}$	68	V
$V_{GS(th\_Typ)}$	3.0	V
$I_D(@V_{GS}=10V)$	80	A
$R_{DS(ON\_Typ)}(@V_{GS}=10V)$	7.2	mΩ



TO-220-3L Top View



Pin Assignment



Schematic Diagram

### Ordering Information

Device	Marking	MSL	Form	Package	Reel(pcs)	Per Carton (pcs)
JMTC6888A	JMTC6888A	NA	Tape&Reel	TO-220-3L	50	5000

### Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-to-Source Voltage	68	V
$V_{GS}$	Gate-to-Source Voltage	$\pm 20$	V
$I_D$	Continuous Drain Current	$T_C = 25^\circ\text{C}$	A
		$T_C = 100^\circ\text{C}$	
$I_{DM}$	Pulsed Drain Current <sup>(1)</sup>	Refer to Fig.4	A
$E_{AS}$	Single Pulsed Avalanche Energy <sup>(2)</sup>	159	mJ
$P_D$	Power Dissipation	$T_C = 25^\circ\text{C}$	W
		$T_C = 100^\circ\text{C}$	
$T_J, T_{STG}$	Junction & Storage Temperature Range	-55 to 150	$^\circ\text{C}$

### Thermal Characteristics





Symbol	Parameter	Max	Unit
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient <sup>(3)</sup>	74	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance, Junction to Case	1.3	

**Electrical Characteristics** ( $T_J = 25^\circ\text{C}$  unless otherwise specified)







Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
V <sub>(BR)DSS</sub>	Drain-Source Breakdown Voltage	I <sub>D</sub> = 250μA, V <sub>GS</sub> = 0V	68	-	-	V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> = 68V, V <sub>GS</sub> = 0V	-	-	1.0	μA
I <sub>GSS</sub>	Gate-Body Leakage Current	V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±20V	-	-	±100	nA
On Characteristics						
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA	2.1	3.0	3.9	V
R <sub>DS(ON)</sub>	Static Drain-Source ON-Resistance <sup>(4)</sup>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 30A	-	7.2	9.4	mΩ
Dynamic Characteristics						
R <sub>g</sub>	Gate Resistance	f = 1MHz	-	0.8	-	Ω
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 34V, f = 1MHz	3010	4214	5689	pF
C <sub>oss</sub>	Output Capacitance		152	213	287	pF
C <sub>rss</sub>	Reverse Transfer Capacitance		116	162	219	pF
Q <sub>g</sub>	Total Gate Charge	V <sub>GS</sub> = 0 to 10V V <sub>DS</sub> = 34V, I <sub>D</sub> = 30A	51	72	97	nC
Q <sub>gs</sub>	Gate Source Charge		17	24	33	nC
Q <sub>gd</sub>	Gate Drain("Miller") Charge		13	19	25	nC
Switching Characteristics						
t <sub>d(on)</sub>	Turn-On DelayTime	V <sub>GS</sub> = 10V, V <sub>DD</sub> = 34V I <sub>D</sub> = 30A, R <sub>GEN</sub> = 3Ω	-	18	-	ns
t <sub>r</sub>	Turn-On Rise Time		-	27	-	ns
t <sub>d(off)</sub>	Turn-Off DelayTime		-	35	-	ns
t <sub>f</sub>	Turn-Off Fall Time		-	10	-	ns
Body Diode Characteristics						
I <sub>S</sub>	Maximum Continuous Body Diode Forward Current		-	-	80	A
I <sub>SM</sub>	Maximum Pulsed Body Diode Forward Current		-	-	319	A
V <sub>SD</sub>	Body Diode Forward Voltage	V <sub>GS</sub> = 0V, I <sub>S</sub> = 30A	-		1.2	V
trr	Body Diode Reverse Recovery Time	I <sub>F</sub> = 30A, di/dt = 100A/us	19	27	37	ns
Qrr	Body Diode Reverse Recovery Charge		-	34.1	-	nC

- Notes:
1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
  2.  $E_{AS}$  condition: Starting  $T_J = 25^\circ\text{C}$ ,  $V_{DD} = 34\text{V}$ ,  $V_G = 10\text{V}$ ,  $R_G = 25\text{ohm}$ ,  $L = 0.5\text{mH}$ ,  $I_{AS} = 25.34\text{A}$ ,  $V_{DD} = 0\text{V}$  during time in avalanche.
  3.  $R_{\theta JA}$  is measured with the device mounted on a minimum recommended pad of 2oz copper FR4 PCB.
  4. Pulse Test: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 0.5\%$ .

## Typical Performance Characteristics


**Figure 1: Power De-rating**

**Figure 2: Current De-rating**

**Figure 3: Normalized Maximum Transient Thermal Impedance**

**Figure 4: Peak Current Capacity**


## Typical Performance Characteristics


**Figure 5: Output Characteristics**

**Figure 6: Typical Transfer Characteristics**

**Figure 7: On-resistance vs. Drain Current**

**Figure 8: Body Diode Characteristics**

**Figure 9: Gate Charge Characteristics**

**Figure 10: Capacitance Characteristics**


## Typical Performance Characteristics


**Figure 11: Normalized Breakdown voltage vs. Junction Temperature**




**Figure 12: Normalized on Resistance vs. Junction Temperature**




**Figure 13: Normalized Threshold Voltage vs. Junction Temperature**




**Figure 14:  $R_{DS(ON)}$  vs.  $V_{GS}$**




**Figure 15: Maximum Safe Operating Area**




## Test Circuit




**Figure 1: Gate Charge Test Circuit & Waveform**



**Figure 2: Resistive Switching Test Circuit & Waveform**




**Figure 3: Unclamped Inductive Switching Test Circuit & Waveform**



**Figure 4: Diode Recovery Test Circuit & Waveform**

## Package Mechanical Data(TO-220-3L)



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.70		0.90	0.028		0.035
C	0.45		0.60	0.018		0.024
C2	1.23		1.32	0.048		0.052
C3	2.20		2.60	0.087		0.102
D	8.90		9.90	0.350		0.390
E	9.90		10.3	0.390		0.406
F	6.30		6.90	0.248		0.272
G		2.54			0.1	
H	28.0		29.8	1.102		1.173
L1		3.39			0.133	
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
Φ		3.6			0.142	

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.



is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.